

Crossvent 2i+ PackageFor use with the Bunnell Jet Ventilator



The ideal choice no matter which Jet cart you own.

Keeps the conventional ventilator in the same foot print as the Jet.

Doesn't tie up an expensive ICU ventilator.

One blender adjustment supplies both the Crossvent and Jet.

Flow sensor can be added to the Crossvent to provide transition to a conventional ventilator and patient triggered ventilation if desired. This keeps the bedside uncluttered; the Jet and Crossvent move out only when the ICU ventilator moves in.

Contact: Michael MacGregor m.macgregor@biomeddevices.com 317-297-2050 or 800-224-6633 x243

Crossvent 2i+ Package For use with the Bunnell Jet Ventilator

Key Features

Modes of Ventilation:

Pressure Limited/ Continuous

Flow

Exhaled Volume Monitoring

Built-In Alarms

Battery Backup

Reliable

Easy to Use

All Models Include

Infant Test Lung

Pneumotach

Oxygen Sensor Cell

DEVICES

Instruction & Service Manual

Charger



Pressure Support | Flow Trigger

Monitors/Alarms .

Peak Pressure | Rate | Oxygen Low Battery | Exhaled Tidal Volume

Exhaled Minute Volume

Physical Characteristics

Width 8.4" (21.3 cm) Depth 4.4" (11.2 cm)

Bio-Med Devices Inc.

International@biomeddevices.com

Specifications

Parameter Rate 5-150 bpm

I-150 in CMV Mode

Tidal Volume 5-750ml

Inspiratory Time 0.10 - 3.0 seconds

Base Flow 2.5 lpm

Flow Rate 1-15 lpm

17-55 psi (117-380 kPa) Pneumatic Power

Source

1-15 lpm Continuous Flow

Peak Pressure 0-80 cmH2O PEEP Pressure 0-20 cmH2O 100 cmH2O Maximum Safety

Pressure

0-20 Flow Trigger

(sensitivity scale)

0-50 cmH2O Pressure Support

SIMV Rate 0.6-50 bpm O2 Sensor 21-100%

Pulsatile/Constant Flow | Assist Control | SIMV | CPAP |

PEEP/CPAP | Mean Pressure

Height: 7.5" (19.1 cm) Weight 7.65 lbs (3.5kg)

61 Soundview Road Guilford, CT 06437

Telephone: I-800-224-6633 or 203-458-0202 Fax: 203-458-0440 Website: www.biomeddevices.com E-mail: custserv@biomeddevices.com





2200KC Crossvent 2i+ Stand-Alone 2200KCB Crossvent 2i+ Stand-Alone w/ Blender

Ordering Options

Newer/Wider/Shorter Cart

•2200KCB •1046 •1013 •2016	Crossvent 2i+ Infant Vent w/ Built-in Blender Adapter tee power takeoff for Jet gas connection 15" dual coiled air/oxygen hose dual flow meter attachment (connects flow meters
2010	to blender)
•2014B	18" stainless steel pole and flange assembly
•2013T	tilt mount I" pole vent bracket (angles vent upwards better screen viewing position)
•1042/1043	Ohmeda style (round) oxygen and air quick connect
or	fittings
•1044/1045	Chemtron (rectangular) oxygen and air quick connect fittings

for

Older/taler/Narrow Cart

•2200KCB

• 1046	Adapter tee power takeoff for let gas connection
•1013	15" dual coiled air/oxygen hose
•2016	dual flow meter attachment (connects flow meters
	to blender)
•2014B	18" stainless steel pole and flange assembly
•1042/1043 or	Ohmeda style (round) oxygen and air quick connect fittings
•1044/1045	Chemtron (rectangular) oxygen and air quick

Crossvent 2i+ Infant Vent w/ Built-in Blender

